



BLOWER DC FANS

BA SERIES Ø97×94×33 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 47 Blades
- * Rotational direction CCW view from front inlet side
- * Weight: 208g (7.34 OZ)



BLOWER DC FANS

BA SERIES Ø120×32 mm

- * Material: Impeller & Frame: Plastic (UL 94V-0)
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 37 Blades
- * Rotational direction CCW view from front face
- * Weight: 256 g (9.03 OZ)

ASIA VITAL COMPONENTS CO., LTD. Six Sigma														ASIA VITAL COMPONENTS CO., LTD. Six Sigma															
MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C	MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow		Maximum Air Pressure		Acoustic Noise	Life expectancy L ₁₀ @40°C
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH₂O	IN H₂O	dB-A	hours		PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH₂O	IN H₂O	dB-A	hours	
BA1003_12F	FG/RD	B	12	7.0 to 13.2	2.10	25.20	5500	1.27	44.82	74.80	2.95	62.1	70000		BA12032_12H	FG	B	12	5.0 to 13.2	1.60	19.20	2800	1.098	38.802	34.815	1.370	54.61	70000	
BA1003_12S	FG/RD	B	12	7.0 to 13.2	3.0	36.00	6000	1.47	51.90	88.40	3.48	62.6	70000		BA12032_12U	FG	B	12	5.0 to 13.2	2.00	24.00	3100	1.1994	42.352	40.188	1.5822	56.12	70000	

