

BLOWER DC FANS

BN SERIES Ø175×69 mm

- * Material: Impeller (UL 94V-0) & Frame: Diecast Aluminum
- * Lead Wires: UL 1007 AWG #22 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CW view from front face
- * Weight: 830g (29.28 OZ)



BLOWER DC FANS

BA SERIES 180×180×80 mm

- * Material: Impeller: Plastic (UL 94V-0) Frame: SGCC
- * Lead Wires: UL 1007 AWG #24 or Equivalent
- * Impeller: 11 Blades
- * Rotational direction CW view from front face
- * Weight: 1150 g (40.57 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma														ASIA VITAL COMPONENTS CO., LTD. Six Sigma														
MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L10@40°C	MODEL		Bearing Type	Rated Voltage	Operating Voltage Range		Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L10@40°C			
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH2O	IN H2O	dB-A	hours	PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m³/min	CFM	mmH2O	IN H2O	dB-A	hours	
BN17569_24L	-FG/RD	B	24	14 to 27.6	1.00	24.0	2700	7.892	27.872	29.8	1.173	62.5	70000	BA18080_48U	-FG/RD	B	48	36 to 57	0.55	26.4	4050	3.115	110	54.5	2.146	66.5		
BN17569_24M	-FG/RD	B	24	14 to 27.6	1.50	36.0	3100	9.086	32.086	40.0	1.575	66.0	70000															
BN17569_24H	-FG/RD	B	24	14 to 27.6	2.30	55.2	3600	10.575	37.344	54.1	2.130	69.5	70000															
BN17569_48L	-FG/RD	B	48	32 to 80	0.50	24.0	2700	7.892	27.872	29.8	1.173	62.5	70000															
BN17569_48M	-FG/RD	B	48	32 to 80	0.75	36.0	3100	9.086	32.086	40.0	1.575	66.0	70000															
BN17569_48H	-FG/RD	B	48	28 to 60	1.15	55.2	3600	10.575	37.344	54.1	2.130	69.5	70000															
BN17569_48U	-FG/RD	B	48	28 to 53	1.55	74.4	4000	11.68	41.246	67.4	2.654	72.5	70000															

